

## LF070W.000.xx



### OVERVIEW

70W power supply

Custom made

Modello Model	Tensione di ingresso Input Voltage	Tensione di uscita Output Voltage	Corrente di uscita Output current	Efficiency	Stand By power loss
LF070W.000.12	100-240Vac	12Vdc	5,8 A	86%	0,12W
LF070W.000.24	100-240Vac	24Vdc	2,91 A	88%	0,12W
LF070W.000.36	100-240Vac	36Vdc	1,94 A	88,5%	0,12W
LF070W.000.48	100-240Vac	48Vdc	1,45 A	89%	0,12W

PROTECTIONS
Under/Overtoltage protection
Overload/Short circuit protection

CERTIFICATIONS Compliance with:				
EN62368	EN60950	EN60335	EN61558	IEC/EN 60335-2-75
IEC/EN 61000-3-2	IEC/EN 61000-4-2	IEC/EN 61000-4-4	IEC/EN 61000-4-6	IEC/EN 61000-6-2
IEC/EN 61000-3-3	IEC/EN 61000-4-3	IEC/EN 61000-4-5	IEC/EN 61000-4-11	IEC/EN 61000-6-3

CONNECTIONS	
Input	Terminal Block 2 PIN
Output	Terminal Block 2 PIN

DIMENSIONS AND WEIGHT	
Dimensions (L x W x H)	76 x 51 x 27 mm
Weight	~80g

EMC EMISSION Compliance with:
EN55032
GB9254
Class B
EN55014
EN61000-3-2,-3

EMC IMMUNITY Compliance with:
EN61000-4-2,3,4,5,6,8,11 EN61000-6-2 (EN50082-2)
heavy industry level, criterial A, EAC TP TC 020

