

LF150W.000.xx



OVERVIEW

150W power supply

Able to deliver 175W for few seconds

Custom made

Modello Model	Tensione di ingresso Input Voltage	Tensione di uscita Output Voltage	Corrente di uscita Output current	Efficiency	Stand By power loss
LF150W.000.12	100-240Vac	12Vdc	12,5 A	87,5%	0,12W
LF150W.000.24	100-240Vac	24Vdc	6,25 A	89%	0,12W
LF150W.000.36	100-240Vac	36Vdc	4,16 A	89%	0,12W
LF150W.000.48	100-240Vac	48Vdc	3,12 A	90%	0,12W

PROTECTIONS
Under/Overtoltage protection
Overload/Short circuit protection

CERTIFICATIONS Compliance with:				
EN62368	EN60950	EN60335	EN61558	IEC/EN 60335-2-75
IEC/EN 61000-3-2	IEC/EN 61000-4-2	IEC/EN 61000-4-4	IEC/EN 61000-4-6	IEC/EN 61000-6-2
IEC/EN 61000-3-3	IEC/EN 61000-4-3	IEC/EN 61000-4-5	IEC/EN 61000-4-11	IEC/EN 61000-6-3

CONNECTIONS	
Input	Terminal Block 3 PIN
Output	Terminal Block 2 PIN

DIMENSIONS AND WEIGHT	
Dimensions (L x W x H)	115 x 67 x 35 mm
Weight	~300g

EMC EMISSION Compliance with:
EN55032
GB9254
Class B
EN55014
EN61000-3-2,-3

EMC IMMUNITY Compliance with:
EN61000-4-2,3,4,5,6,8,11 EN61000-6-2 (EN50082-2)
heavy industry level, criterial A, EAC TP TC 020

